

LS-A2MS Flashlight



Main features:

- Waterproof housing with a phosphorescent silicone cover.
- Built-in integrated Motion Sensing Alarm (PASS).
- "Warm" light delivers superior smoke penetration, richer color rendering, and optimal visual comfort.
- Two independent light sources, each controlled by a dedicated, large, glove-friendly button.
- Magnetic charging port allows for convenient in-device charging without removing the batteries.
- Operates on rechargeable Li-ion batteries (2x18650 or 2x26650) or standard batteries (6xAAA). Features an integrated battery status indicator.
- Mounts securely to turnout gear using a rugged metal clip and carabiner.



ANSI / NEMA FL1 SPECIFICATIONS									
MODES	TURBO			MEDIUM			ECO		
RUNTIME*	Spot LED	Flood LED	Both	Spot LED	Flood LED	Both	Spot LED	Flood LED	Both
	3 h	3 h	1 h	28 h	28 h	14 h	125 h	125 h	80 h
OPTICS	Fresnel lens and reflector								
CAPABILITY	20 W (max)								
LIGHT OUTPUT	1014 lm (max)								
DISTANCE	740 m (max)								
INTENSITY	136 757 cd (max)								
COLOR TEMPERATURE	3100 K (±10%)								
BEAM ANGLE	min – 2.4°, max – 68.2°								
IMPACT RESISTANCE	1 m								
WATERPROOF	IP 67, underwater 1 m								
MATERIAL	Aircraft-grade aluminum (Avial)								
BATTERY TYPE	2 Li-ion batteries 18650, 2 Li-ion batteries 26650 or 6 batteries AAA								
SWITCH	3 spot-buttons on the head of the flashlight								
SIZE AND WEIGHT	161 mm x 72 mm x 58 mm, head diameter 65 mm, weight 431 g								
ACCESSORIES	Battery cassettes, battery tubes, leather strap, spare silicone O-rings								

